



### **Stainless Steel Grooved End Fittings Tee**

As the professional manufacture, we would like to provide you Hispeed® STAINLESS STEEL GROOVED END FITTINGS TEE. And we will offer you the best after-sale service and timely delivery. The Hispeed Model SS-10 and SS-20 stainless steel grooved fittings are investment cast in sizes 1" - 8"; SS-11 is investment cast in sizes 1" – 10"; and SS-60 are investment cast in sizes 1"-12". These fittings are supplied in ASTM A351 or A743

austenitic grades CF8 (304) and CF8M (316). Materials are in compliance with NSF/ANSI 372 for potable water service applications. In addition fittings are also available on request in CF3M (316L), 316Ti, 2205 Duplex, 2507 Super Duplex and ASTM CK-3MCuN (UNS J93245) the cast equivalent to 254SMO\* to meet your specific service requirements. All cast fittings feature full flow characteristics and are designed to the same C - E dimensions of standard ductile iron grooved fittings.

#### **Product Description**

You can rest assured to buy Hispeed® STAINLESS STEEL GROOVED END FITTINGS TEE from our factory and we will offer you the best after-sale service and timely delivery. As the professional manufacture, we would like to provide you STAINLESS STEEL GROOVED END FITTINGS TEE. And we will offer you the best after-sale service and timely delivery.

| Nominal Size | Pipe O.D. | SS-20 Tee |        |
|--------------|-----------|-----------|--------|
|              |           | C-E       | Weight |
| in           | in        | in        | Lbs    |
| mm           | mm        | mm        | Kgs    |
| 1            | 1.315     | 2.25      | 0.9    |
| 25           | 33.4      | 57        | 0.4    |
| 1¼           | 1.66      | 2.75      | 1.5    |
| 32           | 42.2      | 70        | 0.7    |
| 1½           | 1.9       | 2.75      | 1.8    |
| 40           | 48.3      | 70        | 0.8    |
| 2            | 2.375     | 3.25      | 2.4    |
| 50           | 60.3      | 83        | 1.1    |
| 2½           | 2.875     | 3.75      | 5.5    |
| 65           | 73        | 95        | 2.5    |
| 76.1 mm      | 3         | 3.75      | 5.5    |
|              | 76.1      | 95        | 2.5    |
| 3            | 3.5       | 4.25      | 4.6    |
| 80           | 88.9      | 108       | 2.1    |
| 4            | 4.5       | 5         | 7.5    |
| 100          | 114.3     | 127       | 3.4    |
| 139.7 mm     | 5.5       | 5.5       | 12.3   |
|              | 139.7     | 140       | 5.6    |
| 5            | 5.563     | 5.5       | 12.8   |
| 125          | 141.3     | 140       | 5.8    |
| 165.1 mm     | 6.5       | 6.5       | 19.8   |
|              | 165.1     | 165       | 9      |
| 6            | 6.625     | 6.5       | 21.3   |
| 150          | 168.3     | 165       | 9.7    |
| 8            | 8.625     | 7.75      | 41.4   |
| 200          | 219.1     | 197       | 18.8   |
| 200 JIS      | 8.516     | 7.75      | 30.4   |
|              | 216.3     | 197       | 13.8   |